

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 810 590 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
09.06.1999 Bulletin 1999/23

(51) Int Cl.⁶: G11B 7/24, G11B 7/00,
G11B 7/09

(43) Date of publication A2:
03.12.1997 Bulletin 1997/49

(21) Application number: 97303518.1

(22) Date of filing: 22.05.1997

(84) Designated Contracting States:
DE FR GB

(30) Priority: 28.05.1996 US 654408

(71) Applicant: International Business Machines
Corporation
Armonk, N.Y. 10504 (US)

(72) Inventors:
• Rosen, Hal Jervis
Los Gatos, California 95032 (US)

• Rubin, Kurt Allan
Santa Clara, California 95050 (US)
• Tang, Wade Wai-Chung
San Jose, California 95119 (US)

(74) Representative: Ling, Christopher John
IBM United Kingdom Limited,
Intellectual Property Department,
Hursley Park
Winchester, Hampshire SO21 2JN (GB)

(54) Optical data storage system with multiple rewritable phase-change recording layers

(57) A multiple recording layer rewriteable phase-change optical disk (12) and disk drive uses a reverse writing type of reversible phase-change material as the recording layer (53) nearest the incident laser light. The disk has a light-transmissive substrate (50) onto which the laser light is incident. The substrate supports at least two spatially-separated multilayer recording stacks (90, 92), each stack including an active recording layer (53, 64) of reversible or rewriteable phase-change material. The recording stack (90) located nearest the substrate (50) on which the laser light is incident includes a reverse writing type of reversible phase change material, i.e., a phase-change material with an amorphous starting phase that is recorded onto by laser heating that converts data regions to the crystalline phase. This first recording layer (50) has a dielectric layer (51) in contact with it that has a high index of refraction relative to the adjacent recording layer and that acts as an optical interference film to provide a constructive optical interference effect in the recording stack. The optical interference film optimizes the contrast, reflectivity, and transmissivity of the recording stack. The optical interference film is also nonabsorbing so that laser light can pass through it to focus on a recording layer (64) in a farther recording stack (92). This allows the farther recording layer to be written using reasonable laser power.




FIG. 5

EP 0 810 590 A3

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 30 3518

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

15-04-1999

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0337553	A	18-10-1989	DE	68911014 D	13-01-1994
			DE	68911014 T	26-05-1994
			JP	2009682 A	12-01-1990
			US	5045373 A	03-09-1991

US 5414451	A	09-05-1995	JP	5101398 A	23-04-1993
			US	5614938 A	25-03-1997

EP 0426437	A	08-05-1991	JP	3144938 A	20-06-1991
			DE	69032173 D	30-04-1998
			DE	69032173 T	08-10-1998
			US	5192644 A	09-03-1993

US 5383172	A	17-01-1995	CN	1083615 A	09-03-1994
			EP	0583845 A	23-02-1994
			JP	6168446 A	14-06-1994
			SG	44850 A	19-12-1997
			US	5479392 A	26-12-1995

US 4984231	A	08-01-1991	JP	2075251 C	25-07-1996
			JP	7111788 B	29-11-1995
			JP	63181137 A	26-07-1988

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82